

## Data sheet

## Climatic Chamber KK 500 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

### Advantages of the SMART PRO controller:

- large (7"), clear, full colour touch screen
- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarm
- Admin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download




Smart PRO - preview screen

**TECHNICAL DATA**

|                      |                             |
|----------------------|-----------------------------|
| air convection       | forced                      |
| chamber capacity [l] | 462                         |
| working capacity [l] | 392                         |
| controller           | microprocessor PID          |
| display              | 7" full colour touch screen |

**TEMPERATURE AND HUMIDITY**

|  |                                 |
|--|---------------------------------|
| temperature range [°C]                           | 0...+60                         |
| temperature resolution every ... [°C]            | 0,1                             |
| temperature variation at 25°C and 60%rH [+/-°C]* | 2,0                             |
| relative humidity range [%]                      | 30...90 (see chart for details) |
| humidity resolution every ... [%]                | 1,0                             |
| humidity variation at 25°C and 60% rH [%rH]      | 5,0                             |
| over temperature protection                      | class 3.3 to DIN 12880          |


**CHAMBER**


|                 |   |
|-----------------|---|
| door            | double (external solid, internal glass) / external glass (option) |
| <b>interior</b> |   |
| Smart PRO       | acid-proof stainless steel to DIN 1.4301                          |
| IG Smart PRO    | acid-proof stainless steel to DIN 1.4301                          |
| <b>housing</b>  |   |
| Smart PRO       | powder coated sheet   |
| IG Smart PRO    | stainless steel linen finish                                      |

**overall dims [mm] /1/**

|          |      |
|----------|------|
| A width  | 660  |
| B height | 1990 |
| depth C  | 1010 |

**internal dims [mm]**

|          |      |
|----------|------|
| width D  | 470  |
| width D' | 510  |
| height E | 1510 |
| depth F  | 600  |
| height I | 1360 |



|  |        |
|--|--------|
| shelves (standard   max)                 | 3   11 |
| max shelf workload [kg] /2/              | 20     |
| - reinforced shelf version (PW) [kg] /3/ | 100    |
| max unit workload [kg]                   | 100    |
| weight [kg]                              | 130    |

**ELECTRICAL PARAMETERS**

|                   |                   |
|-------------------|-------------------|
| power supply      | 230V 50-60Hz      |
| nominal power [W] | 1850              |
| refrigerant       | R290 / GWP=3      |
| warranty          | 24 months         |
| manufacturer      | POL-EKO-APARATURA |

all the above technical data refer to standard units (without optional accessories)

\* - variation (K) calculated for chamber as:  $K = \frac{T_{\text{average max.}} - T_{\text{average min.}}}{2}$

\*\* - other power supplies on request


1 - depth doesn't include 50 mm of power cable

2 - on uniformly loaded surface

3 - reinforced shelf

4 - reinforced version

## OPTIONS AND ACCESSORIES




Order number: \*/A

Door with viewing window




















Order number: \*/P INOX

Stainless steel wire shelf INOX



Order number: \*/PP

Perforated shelf

|   |                                  |  |
|---|----------------------------------|--|
|    | Order number: */PW               | Reinforced shelf                         |
|    | Order number: KUW GN*/*          | Stainless steel cuvettes                 |
|    | Order number: */FIT              | Phytotron system                         |
|    | Order number: FIT/R3             | FIT panels independent control           |
|    | Order number: GNZ                | Internal socket                          |
|    | Order number: KK/CP              | Low water level sensor                   |
|   | Order number: BRT*/L or IQ/OQ/PQ | Calibration and IQ, OQ, PQ qualification |
|  | Order number: BPP 12             | Battery backup for display               |
|  | Order number: PORT ALARM         | Dry alarm contact                        |
|  | Order number: USBK               | USB cable                                |
|  | Order number: LANK               | LAN cable                                |
|  | Order number: OCZ/20             | Non-standard access port 20 mm           |
|  | Order number: OCZ/30             | Additional access port 30 mm             |
|  | Order number: OCZ/60             | Non-standard access port 60 mm           |
|  | Order number: OCZ/100            | Non-standard access port 100 mm          |
|  | Order number: KK/Z               | Container for deionised water            |
|  | Order number: KD                 | Access control                           |



Order number: CCTV

Camera inside the chamber



Order number: CCTV CAM

Additional camera